



TECHNICAL SPECIFICATIONS

Model	MM200	MM300	MM300HD	MM500	MM500HD	MM1200
<b>Tank Capacity</b>	200 lbs/90kg	300 lbs (136 kg)	300 lbs (136 kg)	500 lbs (226kg)	500 lbs (226kg)	1200lbs (544kg)
<b>Pump Type &amp; Size</b>	1 ½" Gear	1 ½" Gear	1 ½" Gear	1 ½" Gear	1 ½" Gear	1 ½" Gear (2)
<b>Melt Rate /hr</b>	200 lbs (90kg)	300 lbs (136 kg)	300 lbs (136 kg)	500 lbs (226kg)	500 lbs (226kg)	1200lbs (544kg)
<b>PUR Capable</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Power Requirements</b>	240 or 480V 3 Ø	240 or 480V 3 Ø	240 or 480V 3 Ø	240 or 480V 3 Ø	240 or 480V 3 Ø	480V 3 Ø
<b>Amps</b>	60	75	80	90	95	175
<b>Motor Size DC</b>	1 HP	1 HP	2 HP	1 HP	2 HP	2 HP
<b>Wattage</b>	12K	18K	18K	27K	27K	108K
<b>Temperature control</b>	Electronic -PID W/ Power Limit	Electronic -PID W/ Power Limit	Electronic -PID W/ Power Limit	Electronic -PID W/ Power Limit	Electronic -PID W/ Power Limit	Electronic -PID W/ Power Limit
<b>Weight Lbs.</b>	300	350	375	400	425	1700
<b>Viscosity Range CPS</b>	100 - 200K	100 - 200K	100 - 3.1M	100 - 200K	100 - 3.1M	100 - 200K
<b>Temp Range</b>	32º - 550º F	32º - 550º F	32º - 550º F	32º - 550º F	32º - 550º F	32º - 550º F
<b>Dimensions</b>	41" x 30" x 30"	41" x 30" x 30"	41" x 30" x 30"	41" x 30" x 30"	41" x 30" x 30"	71" x 50" x 50"

**Batson Group, Inc.**

PO Box 3978 \* Greenville, SC 29608

P: 864-242-5262 \* F: 864-271-4535

E-mail : [batson@lpmatson.com](mailto:batson@lpmatson.com)

Website : [www.lpmatson.com](http://www.lpmatson.com)